## SOTTOZERO SNOW S



It is a specific tyre for full snow road conditions. It has narrow blocks and deep grooves. This tyre has been designed for use on 100% snow conditions.

Studding: Max protrusion 2 mm Stud length 15mm

SIZE	VERSION	ø mm D	SECTION WIDTH mm C	TREAD WIDTH mm Cb	ROLLING CIRCUMFERENCE	RIM	NUMBER of studs
135/85R15	SA1	620	130	95	1950	5	228
135/90R16	S1	648	140	100	2035	5	228

## **SOTTOZERO SNOW**



This tyre is characterized by a tread pattern ensuring a perfect adaptability to different types of surfaces. It has a dense siping in the center for better traction and braking and more robust blocks on the shoulder for increased stability. The shoulder and intermediate tread blocks have the stud position indicated. This tyre has been designed for use on mixed conditions up to 30/40% snow/ice and asphalt. Sottozero Snow is designed for 2WD and 4WD cars.

Studding: Max protrusion 2 mm Stud length 15mm

SIZE	VERSION	ø mm D	SECTION WIDTH mm C	TREAD WIDTH mm Cb	ROLLING CIRCUMFERENCE	RIM	NUMBER of studs
185/45R16	Sottozero B	620	199	170	1900	6.5	222
195/45R17	Sottozero	625	203	185	1965	7	234
235/40R18	Sottozero B	650	222	190	2045	8	200

These sizes are available in studded and non-studded versions.



## **SOTTOZERO ICE J1**



It is a studded "Sweden" tyre, with a directional asymmetric design which is ideal for snow-covered and icy surfaces. Its specific orientation of the tread blocks together with the patented Pirelli studding process guarantees the best stability and grip of the studs, even in the most extreme surface conditions. Sottozero Ice JI is designed for 4WD.

SIZE	VERSION	ø mm D	SECTION WIDTH mm C	TREAD WIDTH mm Cb	ROLLING CIRCUMFERENCE	RIM	NUMBER of studs
205/65R15	Sottozero Ice J1	650	202	145	2045	7	384

## **SOTTOZERO ICE WJ**



This asymmetric tyre is ideal for snow-covered and icy surfaces. It is a studded "Sweden" tyre, whose specific orientation of the tread blocks along with the patented Pirelli studding process guarantees the best stability and grip of the studs, even in the most extreme surface conditions.

SIZE	VERSION	ø mm D	SECTION WIDTH mm C	TREAD WIDTH mm Cb	ROLLING CIRCUMFERENCE	RIM	NUMBER of studs
185/65R15	Sottozero Ice WJ	630	190	140	1980	6.5	360

